White Matte Vinyl SY-4041

Application:

Wall or ceiling decoration coating, on a flat surface, event stands, indoor and outdoor frontlight environments, promotional adhesive, POS customizations, signage and etc. Not suitable for application on rough surfaces.

Conditions of use:

The user is fully responsible for the suitability of the product for the intended use, we recommend carrying out application tests. Warranties will only be offered through a contract signed between the parties, based on technical tests by the competent bodies

White Matte Vinyl SY-4041

White Matte Vinyl SY-4041		
FRONT	PVC FILM	WHITE MATTE MONOMERIC
	GRAMMAGE	100 (+/-10%)
	THICKNESS	100 (+/-10%)
ADHESIVE	DESCRIPTION	TRANSPARENT SOLVENT
	GRAMMAGE	20 (+/-15%)
	TEMPERATURE (°c)	Min.10
	HEAT RESISTANCE (°c)	Max +80
	COLD RESISTANCE (°c)	Max10
LINER	PVC FILM	White siliconized paper on one side
	GRAMMAGE	140 (+/-10%)
	THICKNESS	122 (+/- 10%)
Print	Solvete, Eco-Solvent, sérigraphie, Latex and UV	
Clipping	Electronic and Manual	
Durability	1 year if stored properly	
°C storage	15° C to 30° C humidity 50 to 70%	





